


Pressure Washer, Single Phase, TEFC and ODP

1-1/2 thru 5 Hp

NEMA 56 thru 184TC



Applications: Pressure washers, steam cleaners, portable and self contained stationary system for direct drive mount and doubled mount designs.

Features: Ball bearing design. 1 1/2 horsepower ratings are rated at 14 amps or less on 115 volts. Manual thermal overload located in the conduit box. UL and CSA recognized component approval. Capacitor start, capacitor run (two value capacitor).

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Totally Enclosed Fan Cooled											
1 1/2	3600	56	PL3513M	634	K	13.25	39	75.5	115/230	6.6	
	1800	56	PL3514M	842	K	14.12	50	82.5	115/230	6	
2	3600	56	PL3515M	767	K	13.25	43	77	115/230	8.8	1
	1800	56HZ	L3516TM	1,043	K	13.31	46	82.5	208-230	8.1	1, 57
3	3600	56	PL3519M	841	K	14.12	52	85.5	230	12.5	1, 30
	1800	184T	L3609TM	1,152	L1	16.54	95	78	115/230	14.5	2, 20
5	3600	184T	L3608TM	1,326	L1	18.05	92	83	230	19.5	2, 20
	1800	184T	L3612TM	1,339	L1	18.05	100	80	230	23	2, 20
Totally Enclosed Fan Cooled, C-Face											
1 1/2	3600	56C	PCL3513M	679	K	13.25	39	75.5	115/230	6.6	
	1800	56C	PCL3514M	885	K	14.12	51	82.5	115/230	6	
2	3600	56C	PCL3515M	805	K	13.24	43	77	115/230	8.8	1
	1800	145TC	CL3516TM	1,052	L1	14.16	52	78	208-230	8.3	1
3	3600	56C	PCL3519M	882	K	14.12	52	85.5	230	12.5	1, 30
	1800	184TC	CL3619TM	1,368	L1	16.54	81	81.5	230	13.2	2, 20
5	3600	184TC	CL3608TM	1,482	L1	18.05	102	83	230	19.5	2, 20
	1800	184TC	CL3612TM	1,434	L1	18.05	101	80	230	23	2, 20
Open Drip Proof											
1 1/2	3600	56H	PL1313M	552	K	11.75	37	75.5	115/230	6.6	36
	1800	56	PL1319M	732	K	12.06	42	74	115/230	7	
2	3600	56	PL1317M	719	K	12.06	43	77	115/230	8.8	
	1800	56	PL1322M	767	K	12.94	47	78.5	115/230	9.2	
3	3600	56	PL1326M	794	K	12.94	52	85.5	230	12.5	30
	1800	184T	L1408TM	958	L1	15.00	78	78	115/230	16	
5	3600	56/56H	PL1327M	818	K	13.81	57	74.2	230	23	2, 20, 30, 36
	1800	184T	L1410TM	1,165	L1	16.50	90	82.5	230	23	1, 30
Open Drip Proof, C-Face											
1 1/2	3600	56C	PCL1313M	598	K	12.06	39	75.5	115/230	6.6	
	1800	56C	PCL1319M	767	K	12.06	43	74	115/230	7	
2	3600	56C	PCL1317M	767	K	12.06	43	77	115/230	8.8	
	1800	56C	PCL1322M	795	K	12.94	48	78.5	115/230	9.2	
3	3600	56C	PCL1326M	841	K	12.94	52	85.5	230	12.5	30
	1800	184TC	CL1408TM	1,012	L1	15.00	87	78	115/230	16	
5	3600	56HCY	PCL1327M	861	K	14.11	58	74.2	230	23	2, 20, 30, 37, 47
	1800	184TC	CL1410TM	1,220	L1	16.50	99	82.5	230	23	1, 30

(a) See notes on inside back flap.